

LIFTPOD 1.2 m



STANDARD SPECIFICATIONS

Performance

Max working height	3.2 m
Max platform height	1.2 m
Closed platform height	0.39 m (on castors) 0.36 m (on legs)
Platform dimensions L x W	0.58 m x 0.4 m
Working footprint	0.99 m x 0.77 m (unfolded)
Safe working load	150 kg (1 person + tools)
Maximum manual force	200 N
Maximum gradient for operation	0.5°
Maximum wind force	Internal use only 0 m/s

Closed dimensions

Length	0.6 m
Width	0.77 m
Height	1.6 m (on castors)
Weight	180 kg

MADE FOR SOFT FACILITIES MAINTENANCE

- Intuitive and easy to operate
- Foldable for compact storage
- Stylish design
- Public space friendly
- Smooth touch points
- One person operation
- Inclusive for all types of operators
- 24/7 availability – manually operated, no charging required
- Designed to help reduce biomechanical risk factors for lumbar disc strain by allowing upright, adjustable, ergonomic working conditions

CHARACTERISTICS

- Sustainable – patented non-powered lift
- Designed with no scheduled maintenance
- Lightweight, easy to manoeuvre when folded or unfolded
- Low centre of gravity for solid vertical work
- Sturdy ground contact during operation
- Spirit level on base
- 360-degree hands free operation

KEY SPECIFICATIONS

Platform carrying capacity:

150 kg

Working Height:

3.2 m

Dimension:

0.618 m x 0.775 m - Folded

0.990 m x 0.775 m - Unfolded

Wheels:

Non-marking, lockable wheels

IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



JLG EMEA BV

Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands

Tel.: +31 (0)23 565 5665

www.jlg.com

An Oshkosh Corporation Company