

Trade Double & Triple Extension Ladders



Specifications

- Warranty: 3-year
- Max Load: 150kg
- Standard: EN131 Professional
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: GB
- Recommended Usage: Regular

Common Dimensions

- Rung Depth: 35mm
- Distance Between Rungs: 250mm

[Representative image of product]

Features

- Commercial strength box section construction
- Twist proof rung joint
- Reduce fatigue with deep, comfortable D-shaped rungs
- Anti-slip rubber feet
- Stabilising bar supplied with ladder - requires fitting before first use

Product Dimensions

SKU	Rungs /Sections	Closed Length (mm)	Last Climbing Height	Approx. Working Height ¹ (mm)	Extended Length (mm)	Width (mm)	Stabiliser Bar Width (mm)	Depth (mm)	Nett Weight (kg)
1102-029	7 x 3	2000	3134	4734	4000	485	1000	200	18.0
1102-030	9 x 2	2500	3106	4706	4000	410	1000	125	11.5
1102-031	11 x 2	3000	4141	5741	5000	410	1000	125	13.3
1102-032	13 x 2	3500	5176	6776	6000	410	1200	125	15.5
1102-033	15 x 2	4000	6212	7812	7000	410	1200	135	20.0
1102-034	17 x 2	4500	7247	8847	8000	410	1200	150	23.8
1102-035	19 x 2	5000	8282	9882	9000	410	1200	150	26.1
1102-036	21 x 2	5500	9317	10917	10000	410	1200	150	31.2
1102-037	9 x 3	2500	4659	6259	5500	485	1200	200	20.0
1102-038	11 x 3	3000	6212	7812	7000	485	1200	200	22.5
1102-039	13 x 3	3500	7765	9365	8500	485	1200	210	28.3
1102-040	15 x 3	4000	9317	10917	9900	485	1200	220	35.5

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.